

PARTICULATE FILTERS

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|--------|------|--|-----------|------------|-----|
| F202N | 1/4" | 5μ filter element, Drain Capacity 0.5 oz. | 150 PSI | 150 PSI | 38 |
| F502N | 1/4" | 5μ filter element, Drain Capacity 2 oz. | 230 PSI | 230 PSI | 77 |
| F503N | 3/8" | 5μ filter element, Drain Capacity 2 oz. | 230 PSI | 230 PSI | 105 |
| F504N | 1/2" | 5μ filter element, Drain Capacity 2 oz. | 230 PSI | 230 PSI | 109 |
| F704N | 1/2" | 5μ filter element, Drain Capacity 5 oz. / Metal Bowl. | 230 PSI | 230 PSI | 141 |
| F704NA | 1/2" | 5μ filter element, Drain Capacity 5 oz. / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| F706N | 3/4" | 5μ filter element, Drain Capacity 5 oz. / Metal Bowl. | 230 PSI | 230 PSI | 141 |
| F706NA | 3/4" | 5μ filter element, Drain Capacity 5 oz. / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| F802N | 1/4" | 5μ filter element, Drain Capacity 2.8 oz. | 230 PSI | 230 PSI | 61 |
| F802NA | 1/4" | 5μ filter element, Drain Capacity 2.8 oz. / auto drain valve. | 175 PSI | 175 PSI | 61 |
| F803N | 3/8" | 5μ filter element, Drain Capacity 2.8 oz. | 230 PSI | 230 PSI | 88 |
| F803NA | 3/8" | 5μ filter element, Drain Capacity 2.8 oz. / auto drain valve. | 175 PSI | 175 PSI | 88 |
| F804N | 1/2" | 5μ filter element, Drain Capacity 2.8 oz. | 230 PSI | 230 PSI | 105 |
| F804NA | 1/2" | 5μ filter element, Drain Capacity 2.8 oz. / auto drain valve. | 175 PSI | 175 PSI | 105 |
| F906N | 3/4" | 5μ filter element, Drain Capacity 11 oz. / Metal Bowl. | 230 PSI | 230 PSI | 162 |
| F906NA | 3/4" | 5μ filter element, Drain Capacity 11 oz. / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 162 |
| F908N | 1" | 5μ filter element, Drain Capacity 11 oz. / Metal Bowl. | 230 PSI | 230 PSI | 183 |
| F908NA | 1" | 5μ filter element, Drain Capacity 11 oz. / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 183 |
| F966N | 3/4" | 5μ filter element : Removes oil, condensed water, and particles >5μ / Metal Bowl / Water Separator. | 230 PSI | 225 PSI | 162 |
| F966NA | 3/4" | 5μ filter element : Removes oil, condensed water, and particles >5μ / Metal Bowl / Water Separator / auto drain valve. | 175 PSI | 175 PSI | 162 |
| F968NA | 1" | 5μ filter element : Removes oil, condensed water, and particles >5μ / Metal Bowl / Water Separator / auto drain valve. | 175 PSI | 175 PAI | 183 |



F202N



F706N




F804N




F906NA



Semi-Auto Drain Valve



Manual Drain Valve



Auto Drain Valve

LUBRICATORS



L202N



L704N

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|-------|------|--|-----------|------------|-----|
| L102N | 1/4" | Air Lubricator : Oil Capacity 0.2 oz, MALE Female NPT. | 150 PSI | 150 PSI | 38 |
| L202N | 1/4" | Air Lubricator : Oil Capacity 1 oz. | 150 PSI | 150 PSI | 38 |
| L502N | 1/4" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 77 |
| L503N | 3/8" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 105 |
| L504N | 1/2" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 105 |
| L704N | 1/2" | Air Lubricator : Oil Capacity 5 oz. / Metal Bowl. | 230 PSI | 230 PSI | 141 |
| L706N | 3/4" | Air Lubricator : Oil Capacity 5 oz. / Metal Bowl. | 230 PSI | 230 PSI | 141 |
| L802N | 1/4" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 61 |
| L803N | 3/8" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 88 |
| L804N | 1/2" | Air Lubricator : Oil Capacity 2.8 oz. | 215 PSI | 215 PSI | 105 |
| L906N | 3/4" | Air Lubricator : Oil Capacity 11 oz. / Metal Bowl. | 230 PSI | 230 PSI | 162 |
| L908N | 1" | Air Lubricator : Oil Capacity 11 oz. / Metal Bowl. | 230 PSI | 230 PSI | 183 |

COALESCING FILTERS



FM968N

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|---------|------|--|-----------|------------|-----|
| FM764N | 1/2" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz metal bowl with visible sight. | 230 PSI | 230 PSI | 141 |
| FM764NA | 1/2" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz metal bowl with visible sight / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FM766N | 3/4" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz metal bowl with visible sight. | 230 PSI | 230 PSI | 141 |
| FM766NA | 3/4" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz metal bowl with visible sight / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FM863N | 3/8" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. | 175 PSI | 175 PSI | 120 |
| FM864N | 1/2" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. | 175 PSI | 175 PSI | 120 |
| FM966N | 3/4" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. | 230 PSI | 230 PSI | 162 |
| FM968N | 1" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. | 230 PSI | 230 PSI | 183 |

| | | | | | |
|---------|----|---|---------|---------|-----|
| FM968NA | 1" | 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve. | 175 PSI | 175 PSI | 183 |
|---------|----|---|---------|---------|-----|

FILTERS REGULATORS

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|---------|------|---|-----------|------------|-----|
| FR202N | 1/4" | 5μ filter element, Drain Capacity 0.5 oz, Mini Regulator 7 - 140 PSI Range. | 150 PSI | 140 PSI | 38 |
| FR502N | 1/4" | 5μ filter element, Drain Capacity 2 oz, Regulator 7 - 225 PSI Range. | 230 PSI | 225 PSI | 77 |
| FR503N | 3/8" | 5μ filter element, Drain Capacity 2 oz, Regulator 7 - 225 PSI Range. | 230 PSI | 225 PSI | 105 |
| FR504N | 1/2" | 5μ filter element, Drain Capacity 2 oz, Regulator 7 - 225 PSI Range. | 230 PSI | 225 PSI | 109 |
| FR724N | 1/2" | 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 225 PSI Range / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FR724NA | 1/2" | 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FR726N | 3/4" | 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 225 PSI Range / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FR726NA | 3/4" | 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FR802N | 1/4" | 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. | 175 PSI | 145 PSI | 61 |
| FR803N | 3/8" | 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. | 175 PSI | 145 PSI | 88 |
| FR804N | 1/2" | 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. | 175 PSI | 145 PSI | 105 |
| FR804NA | 1/2" | 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range, auto drain valve. | 175 PSI | 145 PSI | 105 |
| FR926N | 3/4" | 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 215 PSI Range / Metal Bowl. | 230 PSI | 215 PSI | 162 |
| FR926NA | 3/4" | 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 162 |
| FR928N | 1" | 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 215 PSI Range / Metal Bowl. | 230 PSI | 215 PSI | 183 |
| FR928NA | 1" | 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 183 |



FR202N



FR726NA



FR804NA

COALESCING FILTERS/DESICCANT DRYERS

1. It is recommended to install a standard air filter/water separator in front of the air cleaner / dryer to remove larger debris (>5 μ) and condensed water.
2. It is also recommended to have a shutoff valve upstream of the air cleaner / dryer for easy depressurization for service.
3. Desiccant dryer: Desiccant beads change color from blue to pink when they need to be changed or reactivated.

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|----------|------|--|-----------|------------|-----|
| FLM764N | 1/2" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl. 2. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 80 |
| FLM764NA | 1/2" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl / auto drain valve. 2. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 80 |
| FLM766N | 3/4" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl. 2. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 100 |
| FLM766NA | 3/4" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl / auto drain valve. 2. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 100 |
| FLM796N | 3/4" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl. 2. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 100 |
| FLM796NA | 3/4" | 1. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / Metal Bowl / auto drain valve. 2. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 100 |
| FLM862N | 1/4" | 1. 0.01 μ filter element, Drain Capacity 2.8 oz. 2. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 50 |
| FLM863N | 3/8" | 1. 0.01 μ filter element, Drain Capacity 2.8 oz. 2. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 70 |
| FLM864N | 1/2" | 1. 0.01 μ filter element, Drain Capacity 2.8 oz. 2. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 80 |
| FLM966N | 3/4" | 1. 0.01 μ filter element : Remove 99.99% particles and oil >0.01 μ . / Metal Bowl. 2. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 110 |

| | | | | | |
|---------|----|--|---------|---------|-----|
| FLM968N | 1" | 1. 0.01 μ filter element : Remove 99.99% particles and oil >0.01 μ . / Metal Bowl. 2. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 130 |
|---------|----|--|---------|---------|-----|



FLM863N

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|--------|------|---|-----------|------------|-----|
| LM262N | 1/4" | Desiccant dryer 0.71 oz visible sight. | 145 PSI | 145 PSI | 38 |
| LM764N | 1/2" | Desiccant dryer 5 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 120 |
| LM766N | 3/4" | Desiccant dryer 5 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 137 |
| LM862N | 1/4" | Desiccant dryer 2.8 oz visible sight. | 175 PSI | 175 PSI | 65 |
| LM863N | 3/8" | Desiccant dryer 2.8 oz visible sight. | 175 PSI | 175 PSI | 80 |
| LM864N | 1/2" | Desiccant dryer 2.8 oz visible sight. | 175 PSI | 175 PSI | 80 |
| LM964N | 1/2" | Desiccant dryer 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 140 |
| LM966N | 3/4" | Desiccant dryer 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 150 |
| LM968N | 1" | Desiccant dryer 11 oz visible sight / Metal Bowl. | 225 PSI | 225 PSI | 162 |



LM863N



LM966N



Desiccant

COMBINATION FRC

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|--------|------|---|-----------|------------|-----|
| C202N | 1/4" | 5μ filter element, Drain Capacity 0.5 oz, Oil Capacity 1 oz, 7 - 145 PSI Range. | 150 PSI | 145 PSI | 38 |
| C704N | 1/2" | 5μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz, 7 - 225 PSI Range / Metal Bowl. | 250 PSI | 225 PSI | 141 |
| C704NA | 1/2" | 5μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz, 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| C706N | 3/4" | 5μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz, 7 - 225 PSI Range / Metal Bowl. | 250 PSI | 225 PSI | 141 |
| C706NA | 3/4" | 5μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz, 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| C802N | 1/4" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range. | 175 PSI | 145 PSI | 61 |
| C802NA | 1/4" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range / auto drain valve. | 175 PSI | 145 PSI | 61 |
| C803N | 3/8" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range. | 175 PSI | 145 PSI | 88 |
| C803NA | 3/8" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range / auto drain valve. | 175 PSI | 145 PSI | 88 |
| C804N | 1/2" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range. | 175 PSI | 145 PSI | 105 |
| C804NA | 1/2" | 5μ filter element, Drain Capacity 2.8 oz, Oil Capacity 2.8 oz, 7 - 145 PSI Range / auto drain valve. | 175 PSI | 145 PSI | 105 |
| C906N | 3/4" | 5μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz, 7 - 225 PSI Range / Metal Bowl. | 250 PSI | 225 PSI | 162 |
| C906NA | 3/4" | 5μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz, 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 162 |
| C908N | 1" | 5μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz, 7 - 225 PSI Range / Metal Bowl. | 250 PSI | 225 PSI | 183 |
| C908NA | 1" | 5μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz, 7 - 175 PSI Range / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 183 |



C202N




C704NA



C803N



C906NA



PIGGY BACK FILTERS

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|----------|------|---|-----------|------------|-----|
| FRL202N | 1/4" | Mini two-point type, 5 μ filter element, Drain Capacity 0.5 oz, Oil Capacity 1 oz. | 150 PSI | 145 PSI | 38 |
| FRL724N | 1/2" | Two-point type, 5 μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FRL724NA | 1/2" | Two-point type, 5 μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FRL726N | 3/4" | Two-point type, 5 μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FRL726NA | 3/4" | Two-point type, 5 μ filter element, Drain Capacity 5 oz, Oil Capacity 5 oz / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 141 |
| FRL926N | 3/4" | Two-point type, 5 μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz / Metal Bowl. | 250 PSI | 225 PSI | 162 |
| FR926NA | 3/4" | Two-point type, 5 μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 162 |
| FRL928N | 1" | Two-point type, 5 μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz / Metal Bowl. | 250 PSI | 225 PSI | 183 |
| FRL928NA | 1" | Two-point type, 5 μ filter element, Drain Capacity 11 oz, Oil Capacity 11 oz / Metal Bowl / auto drain valve. | 175 PSI | 175 PSI | 183 |



FRL724N



FRL724NA

FILTER REGULATORS/COALESCING FILTERS/DESICCANT DRYERS

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|-------------|------|---|-----------|------------|-----|
| FR-FLM764N | 1/2" | 1. 5 μ filter element, Drain Capacity 5 oz, Regulator 7 - 225 PSI Range / Metal Bowl. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz Metal Bowl with visible sight. 3. Desiccant dryer 5 oz visible sight / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FR-FLM764NA | 1/2" | 1. 5 μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz Metal Bowl | 230 PSI | 225 PSI | 141 |

| | | | | | |
|-------------|------|--|---------|---------|-----|
| | | with visible sight / auto drain valve. 3. Desiccant dryer 5 oz visible sight / Metal Bowl. | | | |
| FR-FLM794NA | 1/2" | 1. 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz Metal Bowl with visible sight / auto drain valve. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FR-FLM766N | 3/4" | 1. 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 225 PSI Range / Metal Bowl. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz Metal Bowl with visible sight. 3. Desiccant dryer 5 oz visible sight / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FR-FLM766NA | 3/4" | 1. 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz Metal Bowl with visible sight / auto drain valve. 3. Desiccant dryer 5 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FR-FLM796N | 3/4" | 1. 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 225 PSI Range / Metal Bowl. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz Metal Bowl with visible sight. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FR-FLM796NA | 3/4" | 1. 5μ filter element, Drain Capacity 5 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz Metal Bowl with visible sight / auto drain valve. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FR-FLM862N | 1/4" | 1. 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. 3. Desiccant dryer 2.8oz visible sight. | 175 PSI | 145 PSI | 61 |
| FR-FLM863N | 3/8" | 1. 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. 3. Desiccant dryer 2.8oz visible sight. | 175 PSI | 145 PSI | 88 |
| FR-FLM863NA | 3/8" | 1. 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight | 175 PSI | 145 PSI | 88 |

| | | | | | |
|-------------|------|--|---------|---------|-----|
| | | / auto drain valve. 3. Desiccant dryer 2.8 oz visible sight. | | | |
| FR-FLM864N | 1/2" | 1. 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz metal bowl with visible sight. 3. Desiccant dryer 2.8 oz visible sight. | 175 PSI | 145 PSI | 105 |
| FR-FLM864NA | 1/2" | 1. 5μ filter element, Drain Capacity 2.8 oz, Regulator 7 - 145 PSI Range / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight / auto drain valve. 3. Desiccant dryer 2.8 oz visible sight. | 175 PSI | 145 PSI | 105 |
| FR-FLM966N | 3/4" | 1. 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 215 PSI Range / Metal Bowl. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 230 PSI | 215 PSI | 162 |
| FR-FLM966NA | 3/4" | 1. 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 162 |
| FR-FLM968N | 1" | 1. 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 215 PSI Range / Metal Bowl. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 230 PSI | 215 PSI | 183 |
| FR-FLM968NA | 1" | 1. 5μ filter element, Drain Capacity 11 oz, Regulator 7 - 175 PSI Range / Metal Bowl / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 183 |



FR-FLM863N



FR-FLM864N

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|-----------|------|---|-----------|------------|-----|
| FFLM764N | 1/2" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FFLM764NA | 1/2" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FFLM794NA | 1/2" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FFLM766N | 3/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 230 PSI | 225 PSI | 141 |
| FFLM766NA | 3/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FFLM796NA | 3/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 141 |
| FFLM862N | 1/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 2.8 oz visible sight. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 2.8 oz visible sight. 3. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 88 |

| | | | | | |
|-----------|------|--|---------|---------|-----|
| FFLM863N | 3/8" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 2.8 oz visible sight. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. 3. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 88 |
| FFLM864N | 1/2" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 2.8 oz visible sight. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight. 3. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 105 |
| FFLM864NA | 1/2" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 2.8 oz visible sight / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 2.8 oz visible sight / auto drain valve. 3. Desiccant dryer : 2.8 oz visible sight. | 175 PSI | 175 PSI | 105 |
| FFLM966N | 3/4" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 230 PSI | 230 PSI | 162 |
| FFLM966NA | 3/4" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 162 |
| FFLM968N | 1" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 230 PSI | 230 PSI | 183 |
| FFLM968NA | 1" | 1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight / auto drain valve. 2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. | 175 PSI | 175 PSI | 183 |



FFLM966N



FFLMR966N



Desiccant

| MODEL | DESCRIPTION |
|-------|------------------------|
| DC-01 | Desiccant bottle 800g. |
| DC-02 | Desiccant bottle 200g |

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|------------|------|---|-----------|------------|-----|
| FFLMR764NA | 1/2" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. 4. Regulator w/ Gauge 7 - 175 PSI Range. | 175 PSI | 175 PSI | 141 |
| FFLMR766NA | 3/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 5 oz visible sight / Metal Bowl. 4. Regulator w/ Gauge 7 - 175 PSI Range. | 175 PSI | 175 PSI | 141 |
| FFLMR794NA | 1/2" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight / auto drain valve. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight / auto drain valve. 3. Desiccant dryer : 11 oz visible sight / Metal Bowl. 4. Regulator w/ Gauge 7 - 175 PSI Range. | 175 PSI | 175 PSI | 141 |
| FFLMR796N | 3/4" | 1. 5 μ filter element : Remove oil, condensed water and particles >5 μ / 5 oz metal bowl with visible sight. 2. 0.01 μ filter element : Removes 99.99% particles and oil >0.01 μ . / 5 oz metal bowl with visible sight. | 230 PSI | 225 PSI | 141 |

| | | | | | |
|------------|------|---|---------|---------|-----|
| | | <p>3. Desiccant dryer : 11 oz visible sight / Metal Bowl.</p> <p>4. Regulator w/ Gauge 7 - 175 PSI Range.</p> | | | |
| FFLMR796NA | 3/4" | <p>1. 5μ filter element : Remove oil, condensed water and particles >5μ / 5 oz metal bowl with visible sight / auto drain valve.</p> <p>2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 5 oz metal bowl with visible sight / auto drain valve.</p> <p>3. Desiccant dryer : 11 oz visible sight / Metal Bowl.</p> <p>4. Regulator w/ Gauge 7 - 175 PSI Range.</p> | 175 PSI | 175 PSI | 141 |
| FFLMR964NA | 1/2" | <p>1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>3. Desiccant dryer : 11 oz visible sight / Metal Bowl.</p> <p>4. Regulator w/ Gauge 7 - 175 PSI Range.</p> | 175 PSI | 175 PSI | 141 |
| FFLMR966NA | 3/4" | <p>1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>3. Desiccant dryer : 11 oz visible sight / Metal Bowl.</p> <p>4. Regulator w/ Gauge 7 - 175 PSI Range.</p> | 175 PSI | 175 PSI | 162 |
| FFLMR968NA | 1" | <p>1. 5μ filter element : Remove oil, condensed water and particles >5μ / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>2. 0.01μ filter element : Removes 99.99% particles and oil >0.01μ. / 11 oz metal bowl with visible sight / auto drain valve.</p> <p>3. Desiccant dryer : 11 oz visible sight / Metal Bowl.</p> <p>4. Regulator w/ Gauge 7 - 175 PSI Range.</p> | 175 PSI | 175 PSI | 183 |

ACTIVATED CHARCOAL FILTER



FA968N

| MODEL | NPT | DESCRIPTION | MAX INPUT | MAX OUTPUT | CFM |
|--------|------|--|-----------|------------|-----|
| FA764N | 1/2" | Activated charcoal filter element : Absorbs oil vapors and harmful gases / Metal Bowl. | 225 PSI | 225 PSI | 141 |
| FA766N | 3/4" | Activated charcoal filter element : Absorbs oil vapors and harmful gases / Metal Bowl. | 225 PSI | 225 PSI | 141 |
| FA966N | 3/4" | Activated charcoal filter element : Absorbs oil vapors and harmful gases / Metal Bowl. | 225 PSI | 225 PSI | 183 |
| FA968N | 1" | Activated charcoal filter element : Absorbs oil vapors and harmful gases / Metal Bowl. | 225 PSI | 225 PSI | 183 |



D704NA

AUTOMATIC DRAIN

| MODEL | NPT | DESCRIPTION | MAX INPUT |
|--------|------|--|-----------|
| D704NA | 1/2" | <ol style="list-style-type: none"> 1. High inlet pressure support 2. Longer life time 3. Auto drain design 4. Application for any end of pipe system | 175 PSI |